



PAK DETECTOR TAR DETECTOR

Reference	04001504
Colour	Colourless

Product Description

PAK DETECTOR is an aerosol paint that allows the identification of the presence of tar on road surfaces by the detection of PAH compounds (Polycyclic Aromatic Hydrocarbons). Allows for the rapid determination of bituminous materials (for example : asphalt).

The PAK DETECTOR can identify PAHs in tars above 100ppm. It is not an official measurement but only an indication of the presence of tar in the asphalt.

General recommendations for use

- ❖ Do not expose to temperatures above 50°C.
- ❖ Keep away from sources of ignition, heat and direct sunlight.
- ❖ Do not smoke
- ❖ Do not pierce the aerosol
- ❖ Do not burn the aerosol
- ❖ Consult our Safety Data Sheets free of charge on our website www.quickfds.com



Product features

- ❖ Volume: 500 ml NET
- ❖ Packaging : 1 box of 12 products
- ❖ Binding: Thermoplastic Acrylic
- ❖ Pigments: Minerals and organics free of heavy metals (lead, cadmium)
- ❖ Solvents : Specific to dissolve PAHs
- ❖ PAH content > 150ppm
- ❖ Drying time: 15 minutes
- ❖ Operating temperature: -10°C to 50°C.
- ❖ Store the aerosols between 15 and 25°C, away from humidity.

Operating instructions

1. Use HEAD DOWN. Shake well before use.
2. Spray a thin layer on the surface to be treated.
3. Let dry.
4. After use: PURGE HEAD UP
5. If PAHs are present, the white surface will turn yellow/brown (in case of doubt, it is possible to use a UV lamp, which will highlight the presence of PAHs by a yellow-green coloration).

Last update: **May 2020**. This data sheet cancels all previous versions. The information provided is based on our knowledge and tests performed. They in no way exempt the user from knowing and applying all the rules concerning his activity. The user is solely responsible for precautions related to the use of the product. **Dangerous. Observe the precautions for use.**